

## SPECIFICATIONS

Thermodynamic cycle	Diesel 4 stroke	
Air Handling	TCA	
Bore x Stroke	millimeters	104 x 132
Total displacement	liters	4.5
Valves per cylinder	number	4
Cooling System	liquid	
Direction of Rotation (viewed facing flywheel)	CCW	
Compression ratio	18:1	
Injection System	ECR	

EGR -

## PERFORMANCES

Rated power [*]	kW (HP) @ rpm	125 (170) @ 2200
Peak torque	Nm (kgm) @ rpm	710 (80) @ -
High idle speed	rpm	-
Low idle speed	rpm	±750
Minimum starting temperature without auxiliaries	°C	-15°
Oil and oil filter maintenance interval for replacement	hours	500


## STANDARD CONFIGURATION

Flywheel housing	type	SAE 3 - cast iron
Flywheel size	inch	11" ½
Intake manifold location	high / left side	
Exhaust manifold location	high / right side / middle flange	
Turbocharger	Fixed Geometry Turbo	
Turbocharger location	high / right side / back exhaust	
Fan transmission ratio	1.4:1	
Distance between fan - crankshaft centers	millimeters	X=0 Y=296
Fuel filter	number	single cartridge - left side
Fuel prefilter	-	
Fuel Pump	porated into the high pressure pump	
Oil filter	number	single cartridge - right side
Oil sump	steel-front sump-elastic-35° limits continuous in all directions	
Oil vapours blow-by circuit	it filter mounted on flywheel housing	
Oil heat exchanger	oil / water engine cooler	
Oil filler	on valve cover-front position	
Alternator	24 V - 70 A	
Hydraulic steering pump	-	
Wiring harness	engine harness connected to ECU	
Painting color	grey	
Starter	12V - 3kW / 24V - 4kW	
Maximum torque available from crankshaft pulley	Nm	-
Engine stop device	-	

## WEIGHT AND DIMENSIONS


Dimensions	LxWxH (mm)	16 x 687 x 1049
------------	------------	-----------------

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

## POWER & TORQUE



## NOT INCLUDED IN STANDARD CONFIGURATION

Power Take Off (PTO)	-	
PTO - transmission ratio	1.03:1	
PTO - maximum available torque	SAE A 100Nm - 150Nm SAE B 240Nm -	
Battery - minimum capacity recommended	Ah	130 Ah (24 V)
Battery - minimum cold cranking capacity recommended	Ah	24 V - 500 Ah

## LEGEND

Arrangement	Air Handling	Turbocharger	Injection System	Exhaust System
L (in line)	TCA (Turbocharged with aftercooler)	WG (Wastegate)	M (Mechanical)	EGR (Exhaust Gas Recirculation)
V (90° "V" configuration)	TC (Turbocharged)	VGT (Variable Geometry Turbocharger)	ECR (Electronic Common Rail)	SCR (Selective Catalytic Reduction)
	NA (Naturally Aspirated)	TST (Twin Stage Turbocharge)	EUI (Electronic Unit Injector)	
			MPI (Multi Point Injection)	

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



LEGEND

Arrangement	Air Handling	Turbocharger	Injection System	Exhaust System
L (in line)	TCA (Turbocharged with aftercooler)	WG (Wastegate)	M (Mechanical)	EGR (Exhaust Gas Recirculation)
V (90° "V" configuration)	TC (Turbocharged)	VGT (Variable Geometry Turbocharger)	ECR (Electronic Common Rail)	SCR (Selective Catalytic Reduction)
	NA (Naturally Aspirated)	TST (Twin Stage Turbocharge)	EUI (Electronic Unit Injector)	
			MPI (Multi Point Injection)	

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

